Amendments to the Claims

Please amend the claims as follows.

1-35. (canceled)

- 36. (Currently amended) An amusement ride assembly including comprising: a rotatable endless loop cable spanning between end stations; a drive system operable to rotate the loop cable; and a passenger carrier suspended from the cable, including comprising a roller mechanism to enable the passenger carrier to free-roll along the cable and an associated actuatable clamping mechanism to alternatively fix the passenger carrier to the cable; and an electronic control system that is operable to actuate the clamping mechanism either automatically such that the control system actuates the clamping mechanism according to preset programming, or manually where an operator remote from the passenger carrier operates the control system to actuate the clamping mechanism, or both.
- 37. (Currently amended) An amusement ride assembly according to claim 36, including: a wherein the control system arranged is programmed to allow the passenger carrier to free-roll part way along the cable after initial release of the passenger carrier at the commencement of a ride and to then actuate the clamping mechanism to fix the passenger carrier to the loop cable when the passenger carrier has slowed down to less than a predetermined speed.

38. (Cancelled)

- 39. (Currently amended) An amusement ride assembly according claim 38 36, wherein the control system is switchable between an automatic mode in which the control system controls movement of the passenger carrier along the cable according to preset programmed ride settings, and a manual mode in which an operator remote from the passenger carrier controls movement of the passenger carrier along the cable via the control system.
- 40. (Currently amended) An amusement ride assembly according to claim 38 36, wherein

the control system includes <u>comprises</u> one or more sensors arranged to detect any one or more of the following: proximity of the passenger carrier to either of the end stations; actuation of the clamping mechanism; speed of the passenger carrier along the loop cable; and distance travelled by the passenger carrier along the loop cable.

- 41. (Currently amended) An amusement ride assembly according to claim 36[[,]] wherein the passenger carrier also includes <u>further comprises</u> a swivel mechanism which that is operable to rotate the passenger carrier about a substantially vertical axis.
- 42. (Currently amended) An amusement ride assembly according to claim 36[[,]] wherein the drive system is operable to rotate the cable in either direction, and wherein the control system is arranged to operate the drive system to rotate the loop cable in the direction the passenger carrier travels along the cable, at the same time as the passenger carrier travels along the cable.

43. (Cancelled)

44. (Currently amended) An amusement ride assembly according to claim 43 42, wherein the control system is arranged to actuate the clamping mechanism to fix the passenger carrier to the loop cable when the passenger carrier has slowed down to a speed which is similar to substantially the same as the speed of the cable.

45. (Cancelled)

- 46. (Currently amended) An amusement ride assembly according to claim 45, 36 including comprising two passenger carriers, one carried on each side of the loop cable.
- 47. (Currently amended) An amusement ride according to claim 36[[,]] further including comprising one or more intermediate stations located between the end stations and which support the cable intermediate of its length.

- 48. (Currently amended) A method of providing an amusement ride including comprising the steps of: (a) loading a passenger carrier with one or more passengers; (b) allowing the passenger carrier to free-roll under gravity along a span of a loop cable from a position at or toward one station, toward another station; (c) clamping the passenger carrier to the loop cable at a specific point intermediate of the distance between the two stations; and (d) rotating the loop cable to move the passenger carrier further between the stations.
- 49. (Currently amended) A method according to claim 48, including wherein step (c) further comprises the step of clamping the passenger carrier to the loop cable when the speed of the passenger carrier drops to within below a predetermined speed relative to the cable.
- 50. (Currently amended) A method according to claim 48, including further comprising the step of rotating the loop cable in the same direction of travel as the free-rolling passenger carrier.
- 51. (Currently amended) A method according to claim 50, including further comprising the step of clamping the passenger carrier to the loop cable when the speed of the free-rolling passenger carrier is similar to substantially the same as the speed of the cable.
- 52. (Currently amended) An amusement ride assembly including comprising a cascade of two or more stages, each stage including comprising: a rotatable endless loop cable spanning between two stations; and a drive system operable to rotate the loop cable, the ride further including comprising: one or more passenger carriers, which can accommodate one or more passengers, attachable to the loop cables of each stage; and a suspension member which suspends the passenger carrier(s) to the loop cables, wherein the suspension member includes comprises a roller mechanism to enable the passenger carrier(s) to free-roll along the loop cables and a clamping mechanism which can be actuated to alternatively fix the passenger carrier(s) to the loop cables; and an electronic control system that is operable to actuate the clamping mechanism either automatically such that the control system actuates the clamping mechanism according to preset programming, or manually where an operator remote from the passenger carrier(s) operates the control system to actuate the clamping mechanism, or both.

53. (Currently amended) An amusement ride assembly according to claim 52[[,]] wherein the passenger carrier(s) may transfer between loop cables of adjacent stages, and wherein a transfer station is provided between each stage to facilitate the transfer of the passenger carrier(s) between loop cables of adjacent stages.

54. (Cancelled)

- 55. (Currently amended) An amusement ride assembly according to claim 52 53, wherein one or more of the stations may form part of an adjacent stage.
- 56. (New) An amusement ride assembly comprising:
 - a rotatable endless loop cable spanning between end stations;
 - a drive system operable to rotate the loop cable;
- a passenger carrier suspended from the cable, comprising a roller mechanism to enable the passenger carrier to free-roll along the cable and an associated actuatable clamping mechanism to alternatively fix the passenger carrier to the cable; and

an electronic control system that is operable to actuate the clamping mechanism and which is programmed to allow the passenger carrier to free-roll part way along the cable after initial release of the passenger carrier at the commencement of a ride and to then actuate the clamping mechanism to fix the passenger carrier to the loop cable when the passenger carrier has slowed down to less than a predetermined speed.

- 57. (New) An amusement ride assembly comprising:
 - a rotatable endless loop cable spanning between end stations;
 - a drive system operable to rotate the loop cable;
- a passenger carrier suspended from the cable, comprising a roller mechanism to enable the passenger carrier to free-roll along the cable and an associated actuatable clamping mechanism to alternatively fix the passenger carrier o the cable; and

an electronic control system that is operable to actuate the clamping mechanism and which is operable by an operator remote to the passenger carrier to allow the passenger carrier to free-roll part way along the cable after initial release of the passenger carrier at the

commencement of a ride and to then actuate the clamping mechanism to fix the passenger carrier to the loop cable when the passenger carrier has slowed down to less than a predetermined speed.

- 58. (New) An amusement ride assembly according to claim 39 wherein the control system is arranged to switch from the automatic mode to the manual mode on detection of a fault.
- 59. (New) An amusement ride assembly according to claim 36 wherein the control system comprises a control module at each end station, and wherein the control modules are arranged to communicate via a radio link.
- 60. (New) An amusement ride assembly according to claim 59 wherein the control system further comprises a passenger carrier control module located on the passenger carrier that is arranged to generate control signals for actuating the clamping mechanism, and wherein the passenger carrier control module further comprises a radio transmitter/receiver for communicating with at least one end station control module and is arranged to actuate the clamping mechanism in response to signals received from an end station control module.
- 61. (New) An amusement ride assembly according to claim 36 wherein the control system comprises a passenger carrier control module located on the passenger carrier that is arranged to generate control signals for actuating the clamping mechanism based on preset programming of the passenger carrier control module.